

**iDS-7700NXI-I4/16P/X(B)  
DeepinMind SERIES NVR**



## Features and Functions

### Human and Vehicle Analysis

Deep learning-based human and vehicle target classification improves false alarm reduction effect

### Professional and Reliable

- New logical and visualized GUI design
- Dual-OS design to ensure high reliability of system running
- ANR technology to enhance the storage reliability when the network is disconnected

### Video Input and Transmission

- Full channel IP cameras connection
- Connectable to the third-party network cameras

### Compression and Recording

- H.265+ compression effectively reduces the storage space and costs by up to 75%
- Full channel recording at up to 12 MP resolution

### HD Video Output

- HDMI and VGA independent outputs provided
- HDMI Video output at up to 4K resolution

### Storage and Playback

- Up to 4 SATA interfaces for HDD connection
- 16-ch synchronous playback at up to 1080p resolution
- Normal/Important/Custom video playback
- Files management
- HDD health monitoring

### Smart & POS Function

- Supports multiple VCA (Video Content Analytics) events
- Smart search for the selected area in the video; and smart playback to improve the playback efficiency
- POS information overlay on live view and playback
- POS triggered recording and alarm

### Network & Ethernet Access

- Hik-Connect for easy network management
- Gigabit Ethernet network interface
- 16 independent PoE network interfaces are provided




## Specifications

Model	iDS-7716NXI-I4/16P/X(B)		iDS-7732NXI-I4/16P/X(B)	
<b>Face detection and analytics<sup>1</sup></b>	<b>Face picture library</b>	16 libraries		
		100, 000 pictures		
	<b>Face picture comparison alarm</b>	16-ch face pictures comparison alarm, Alarm linkage actions: recording, audio warning, notify surveillance center, send email		
	<b>Face picture search</b>	Search by picture is supported		
	<b>Performance of facial detection and analytics</b>	8-ch human face capture (HD network camera, up to 4 MP, H.264/H.265)		
<b>Human/Vehicle analysis<sup>1</sup></b>	<b>False alarm reduction</b>	Up to 16-ch 2 MP (H.264/H.265) video analysis for human and vehicle recognition to reduce false alarm		
<b>Video/Audio input</b>	<b>IP video input</b>	16-ch		32-ch
		Up to 12 MP resolution		
	<b>Two-way audio</b>	1-ch, RCA (2.0 Vp-p, 1 k Ω)		
<b>Network</b>	<b>Incoming bandwidth</b>	320 Mbps		
	<b>Outgoing bandwidth</b>	256 Mbps		
	<b>Remote connection</b>	128		
<b>Video/Audio output</b>	<b>Recording resolution</b>	12 MP/8 MP/6 MP/5 MP/4 MP/3MP/1080p/UXGA/720p/VGA /4CIF/DCIF/2CIF/CIF/QCIF		
	<b>CVBS output</b>	1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480		
	<b>HDMI1 output resolution</b>	4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz		
	<b>VGA output resolution</b>	1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz, HDMI1/VGA Simultaneous Output		
	<b>HDMI2 output resolution</b>	1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz		
	<b>Audio output</b>	1-ch, RCA (Linear, 1 kΩ)		
<b>Decoding</b>	<b>Decoding format</b>	H.265/H.265+/H.264/H.264+/MPEG4		
	<b>Live view / Playback resolution</b>	12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA /4CIF/DCIF/2CIF/CIF/QCIF		
	<b>Synchronous playback</b>	16-ch		
	<b>Capability</b>	16-ch @ 1080p		
<b>Network management</b>	<b>Network protocols</b>	TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS		
<b>Hard disk</b>	<b>SATA</b>	4 SATA interfaces		
	<b>Capacity</b>	Up to 10 TB capacity for each HDD		
	<b>eSATA</b>	1 eSATA interface		
<b>External</b>	<b>Network interface</b>	1, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface		

<b>interface</b>	<b>Serial interface</b>	RS-485 (half-duplex), RS-232, Keyboard
	<b>USB interface</b>	Front panel: 2 × USB 2.0; Rear panel: 1 × USB 3.0
	<b>Alarm in/out</b>	16/8
<b>PoE interface</b>	<b>Interface</b>	16 RJ-45 10/100 Mbps self-adaptive Ethernet interfaces
	<b>Power</b>	≤ 200 W
	<b>Supported standard</b>	IEEE 802.3 af/at
<b>General</b>	<b>Power supply</b>	100 to 240 VAC, 50 to 60 Hz
	<b>Total power</b>	≤ 350 W
	<b>Consumption (without hard disk and PoE off)</b>	≤ 30 W
	<b>Working temperature</b>	-10 °C to 55 °C (14 °F to 131 °F)
	<b>Working humidity</b>	10 to 90 %
	<b>Chassis</b>	19-inch rack-mounted 1.5U chassis
	<b>Dimensions (W × D × H)</b>	445 × 400 × 71 mm ( 17.5"× 15.7" × 2.8")
<b>Weight (without hard disk)</b>	≤ 5 kg (11 lb)	

1: Facial detection and analytics and human/vehicle analysis cannot be enabled at the same time. Enable one function will make the other one unavailable.

## Physical Interfaces



Index	Description	Index	Description
1	LAN Interface	2	AUDIO OUT
3	AUDIO IN	4	HDMI Interface
5	USB 3.0 Interface	6	RS-232 Serial Interface
7	VGA Output (DB9 Connector)	8	RS-485 Serial Interface
9	Controller Port, Alarm In/Alarm Out	10	GND
11	100 to 240 VAC power supply	12	Power Switch
13	Network Interfaces with PoE function	14	eSATA Interface
15	VIDEO OUT		

## Available Models

iDS-7716NXI-I4/16P/X(B), iDS-7732NXI-I4/16P/X(B)

Distributed by



## HIKVISION®

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Africa**  
T +27 (0) 0351172  
sale.africa@hikvision.com

**Hikvision Europe**  
T +31-23-55-42-770  
info.eu@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Oceania**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision Hong Kong**  
T +852-2151-1761

**Hikvision Middle East**  
T +971-4-8816086  
salesme@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Canada**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
poland@hikvision.com

**Hikvision Korea**  
T +82-31-731-8841  
sales.korea@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision UK**  
T +01628-902140  
support.uk@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com